
CM5016-REAR


Video instructions are available at https://www.fhgroupauto.com/product/honda-accord




Warning

- Machine wash cold, • delicate cycle. Air dry only.
- Avoid sharp objects to protect covers from being scratched/damaged.
- We suggest wearing
 protective eyewear and
 gloves during installation.







(5) Place the Bottom seat covers on the bench seat cushion and push the hook-and-loop straps through the center crevice of your seat. Next, slide the attach clips into the seat crevice to secure the bottom.




To secure the bottom cover, first split your car seat and open the flap on the back of the seat. Then, attach the hook-and-loop straps directly to the back of the backrest.




1) To start, remove the headrest by pushing the release button at the base of the headrest.




2) Slide the backrest 60 side cover onto backrest following the contour of the seat, until it's fully on the backrest. Then, close the hook-and-loop straps near the seatbelt holder and tuck in the reminder fabric in the seat crevice.




(7) To attach both bolster covers, split the backrest and place the cover following the shape of the bolster. Then, slip in the attach clips into the seat crevice and tuck in all the cover edges. Repeat the same process to install the other bolster cover.




Slip on the headrest cover and reattach the headrests. TIP: Starting from either side of the headrest and sliding the cover sideways will help you achieve a secure fit. Repeat same process for all headrests.



(3) Push the rear hook-and-loop straps through the seat crevice. Attach the straps directly to the upholstery of the backseats.



(4) For the Backrest 40 Side, push the rear hook-and-loop straps through the seat crevice. Attach the straps directly to the upholstery of the backseats.



Adjust accordingly, smooth out your custom-fit seat covers, and enjoy!