



Like all FH Group® auto accessories, these custom car seat covers were designed with the utmost precision, created from the highest quality of materials, and produced with the Intent of providing every driver with a failared laxury car experience. With FH Group® you will always Take Pride In Your Ride¹¹.

To register for the Custom Sect Cover Limited Warranty, go to https://www.thgroupauto.com/warranty/





CM5030-FRONT SEAT COVERS


Video instructions are available at

https://www.fhgroupauto.com/product/neoprene-custom-fit-seat-covers-for-2019-2022-hyundai-santa-fe-full-set/




WARNING

- Machine wash cold, delicate cycle. Air dry only.
- Avoid sharp objects to protect covers from being scratched/damaged.
- We suggest wearing protective eyewear and gloves during installation.




2 BACKREST



2 BOTTOM


SEATS



PACKAGE INCLUDES

CONSOLE


COVER




 Detach the headrest from the seat by pressing the button located at the base of the headrest. Note: To fully release the headrest, you will also need to insert a metal pin in the small whole of the headrest base (as shown in the image). Then, simply lift and take off the headrest.




(3) Insert the front hook-and-loop straps through the crevice of the seat and push them until they come out at the back of the seat.




2) Slide the backrest cover over your seat's backrest until it's fully on. Please make sure to follow the seat's contour. Then, tuck in the cover under the headrest base.




From the back of the seat, detach the seat's backrest flap by unclipping the straps from the bottom of the seat. Then, pull the cover straps you pushed through the seat crevice and attach them with the hook-and-loop to the seat's upholstery.




(5) To install the bottom seat cover, place it on the car seat making sure it follows the shape and contour of the seat. Then, push the buckle straps through the seat crevice until they come out at the back of the seat.




Once the cover is on, tuck in the corners of the cover between the seat cushion and the plastic frame. Also, tuck in the small hook-and-loop strap located near the seat belt buckle.




Connect together the front and back buckle straps under the seat as shown in the picture. NOTE: Please make sure the front strap go in between the plastic seat frame and the cushion. Then, tighten up the straps for a secure fit.



Reattach the headrests to the seats and slip on the headrest covers. TIP: Starting from either side of the headrest and sliding the cover sideways will help you achieve a secure fit.



Reattach the seat's flap to its original position by clipping the clips to the bottom of the seat. Then, secure the back of the cover to the seat by attaching the hook-and-loop attachments to the seat upholstery.



Adjust accordingly and smooth out your custom-fit seat cover!